



## CEDAR DOOR COLLECTION

Catalogue 2018-2019

# Life Illuminated

## OUR PASSION IS RELATIONSHIPS, COME IN AND STAY AWHILE, WE'VE BEEN WAITING FOR YOU

Your Premier destination for all things fireside, outdoor living and garage doors. Thank you for making Trinity Fireside this areas leading supplier and installer of Fireplaces, Outdoor Living and Garage Doors. Our wide selection, expertise, and professional service are an integral part of our business relationships, and allow us to provide our customers unmatched value, as well as a high level of trust.

We take pride in our relationships with quality manufacturers, over 150 years of combined industry experience, high levels of certification, and partner with some of the most well known and respected builders and architects in Texas and Oklahoma.

### • Garage Doors and Garage Door Operators

- Distinguished Industry leaders including Wayne Dalton, Mid America Door, Amarr, Liftmaster, Genie and Linear.
- We design, build, and install custom cedar garage doors. Unlike many of our competitors, we utilize commercial-grade hardware components to ensure safety and durability.
- An average of 6 years experience for all installers and service techs.
- Signature Installation Program that ensures safety, performance, and customer satisfaction.

### • Additional Customer Resources

- Dedicated Customer Service and Scheduling staff
- Outside sales force and field superintendents to help you with special products or unusual installation issues.
- Showroom and Inside Sales Consultant to help you and your customers choose the best products based on their needs and budgets
- Wide selection of in-stock products, as well as thousands more available for special order
- Digital photos of every fireplace and garage door installation to ensure quality, accuracy, and safety.



# You Are Always Welcome Here









## TRINITY IRONWOOD CEDAR DOORS

### CUSTOM CEDAR DOORS HANDMADE ON SITE WITH PRIDE BY THE FINEST CARPENTERS IN THE INDUSTRY

**Sections:** Commercial 2" thick 24 gauge painted galvanized ribbed steel finished with vinyl backed polystyrene insulation. Wood is chemically bonded & mechanically fastened.

**Hardware:** Commercial grade track assembly, struts, hinges, bottom and top fixtures with 25,000 life cycle torsion springs. All garage doors are double end stilled for additional strength and also to accommodate the 10 ball bearing 100 lb. rated long stem commercial roller.

**Finish:** Western Cedar rough sawn finish. Please note that all garage doors are furnished unfinished. The garage doors must be sealed, painted and or stained. Stain within 48 hours of installation.

**Warranty:** 1 year on workmanship, hardware, and delamination. 10 year limited warranty on steel section for construction corrosion.

Warping, cupping, & checking are all part of the natural aging process of organic wood products. This is not considered a defect but a true beauty and uniqueness which enhances each door. All wood overlay garage doors, or any other custom made garage doors that are built to customer specifications, or selected from the Ironwood Series styles offered, any special order doors may require a deposit. Trinity Hearth & Home, Inc., reserves the right to make periodic design changes to all door styles and designs without prior notice. All pictures, images and drawings are provided for visual purposes only and please note that not all doors may be replicated as shown due to size, wood species, and other options as selected by the customer. We provide the top new designs for your new hand-crafted cedar garage door including Austin Benbrook, Blanco Crawford, El Paso Fredricksburg, Galveston Justin, and more. We are confident we have the options to provide you with a garage door that you will love!

# TRINITY FIRESIDE

## WHAT CAN WE BUILD FOR YOU

Whatever your style might be, we are here to help create the perfect look to match the uniqueness that sets you apart









# Texas Modern Collection

Gruene




Section JWB16

Pantego




Section JWB17

Amarillo



Section JWB18


Andrews




Section JWB19




Quinlan




Marfa



Luckenbach




Wimberley




# Native Texan Collection


## El Paso




## Benbrook




## Austin




## Crawford




Galveston




Fredricksburg



Justin




Blanco




# Native Texan Collection


Nacogdoches




Mt.Vernon




Odessa




## Weatherford



## San Marcos



## Laredo




# THE WOODSHOP

## SUPERIOR CRAFTSMANSHIP

7,000 sq of our newly designed building is designated to woodworking. Our team utilizes continuous improvement techniques to improve efficiencies, eliminate waste and add value to the finished product.







#### **GARAGE DOOR OPENING FRAMING & CLEARANCE REQUIREMENTS**

**A = Opening Height** - Opening height should finish out as the exact size of the garage door height. Example: a 16 X 7 garage door opening height should be 7'0".

**B = Opening Width** - Opening width should finish out as the exact size of the garage door width. Example: a 16 X 7 garage door opening width should be 16'0".

**C = Headroom** - The distance from the opening height to the ceiling or first obstruction overhead. For standard doors, 12" minimum. When there is less than 12", but at least 6", must use Low Headroom Track option. Note: Add 3" of additional clearance if automatic opener is required.

**D = Backroom** - The depth into the garage from the door opening. Allows for horizontal track clearance so garage door can raise to full open position. Clearance needed is door height + 18" for standard lift doors or door height + 12" for low headroom doors.

**E = Sideroom** - Clearance needed from the edge of the door opening to the first obstruction adjacent to the garage door frame. Clearance needed is 4" for standard lift doors or 6" for low headroom doors.

#### **Additional Requirements Prior to Installation: (by Builder or Homeowner)**

1. Need all framing for garage door as shown above installed.
2. Need garage door frame / fascia installed.
3. Need finished concrete floor.
4. Need sheetrock installed (when applicable).
5. Need clear working space, 10ft into the garage from door opening, entire width of door.
6. 110V receptacle installed in ceiling, centered with garage door, 10"6" back from door top 7ft door height or 11'6" for 8ft door height.
7. Need pre-wiring for photo eyes and wall button station.

A WARM PLACE TO GATHER



[WWW.TRINITYFIRESIDE.COM](http://WWW.TRINITYFIRESIDE.COM)





## TRINITY FIRESIDE

Catalogue 2018-2019